

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

Product name: Woodoc Deep Penetrating Furniture Wax

Product type: Furniture oil

2. COMPOSITION

Substance:

Normal Hydrocarbon blend

3. HAZARDS IDENTIFICATION

Hazardous components: Paraffins/92,2% TLV = 200 ppm

Potential Health effects and main symptoms:

Skin contact: Liquid – can irritate skin or cause dermatitis after prolonged and/or repeated contact.

Eye contact: May cause redness and pain.

Inhalation (Breathing): Irritation of eyes, nose and throat. Aspiration of fluid may cause severe damage.

Ingestion: Liquid – may cause nausea, vomiting and diarrhoea.

Acute over-exposure: May cause nausea, vomiting, headache and depression.

Chronic over-exposure: No chronic effects have been reported.

4. FIRST-AID MEASURES

Ingestion (swallowing): **Do not induce vomiting.** Have victim drink 240-300 ml water. If vomiting occurs have victim lean forward to reduce risk of aspiration. Obtain medical attention.

Skin contact/absorption: Wash gently and thoroughly with water and soap.

Eye contact: Liquid – flush eye(s) with gently flowing lukewarm water. Obtain medical advice immediately.

Inhalation (breathing): If breathing is affected, remove victim to fresh air, call physician, administer oxygen.

Acute over-exposure: Obtain medical attention immediately.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing

media: Foam, CO₂, dry chemical.

Unsuitable extinguishing

media: Water jets.

Protection of fire-fighters: Breathing apparatus independent of the ambient air.

Additional information: Apply cold water in order to cool containers exposed to danger.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Eye/Face/Body: Protective clothing (overall) should be worn.

Hands: Use leather gloves as they provide heat insulation and do not absorb oil.

Environmental

precautions: Prevent material from entering sewers and waterways.

Methods for cleaning up: Absorb with sand, earth or sawdust. Remove to safe area for disposal. Flush area with water.

Additional instructions: Inform authorities in case of large amount leakage.

7. HANDLING AND STORAGE

HANDLING:

Technical measures/ precautions:

Prevent aerosol generation during pumping. Containers and discharge pipes should be earthed. Prevent ignition source.

Safe handling advice:

Usual precautions for handling chemical substance. Consider common hygiene measures for handling chemical substance.

STORAGE:

Storage conditions:

Storage tanks have to be installed and managed accordingly to official regulations. Store at ambient temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures:	General ventilation should be provided to maintain ambient concentration below nuisance levels.
Personal protection:	
Skin:	To avoid any contact with skin, wear protective equipment: clothing such as heavy rubber gloves, leather safety boots, face shields and impervious cotton or cotton blend overalls.
Eye/Face:	Face shields should be worn to protect eyes against splashes.
Respiratory (in detail):	Organic vapour canister or self-contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear liquid
Colour:	Colourless
Odour:	With characteristic odour
Density at 20⁰C:	0,75 kg/litre
Average molecular mass:	Not applicable.
Boiling range at 760mm Hg:	150 ⁰ C – 400 ⁰ C
Solubility in water (20⁰C):	Insoluble in water.
Explosion properties:	Hazard exist when exposed to heat or flame
Pour point:	<35 ⁰ C
Flash point (closed cup):	50 ⁰ C
Auto-ignition temperature:	305 ⁰ C
Flammable limits in air:	Lower 0,8%
% by Volume:	Upper 2,9%

10. STABILITY AND REACTIVITY

Conditions to avoid:	Liquid – prolonged storage 20 ⁰ C above congealing point may interfere with quality.
Hazardous decomposition products:	None
Thermal decomposition:	Approx.250 ⁰ C
Conditions contributing to instability:	Normally stable

11. TOXICOLOGICAL INFORMATION

This product has not been tested. Products of a similar composition did not induce toxic effects.

12. ECOLOGICAL INFORMATION

This product may be toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

Waste: Special waste incineration or by other modes of disposal in compliance with local legislation.
Contaminated packaging: Should be treated equivalent to residual chemical.

14. TRANSPORT INFORMATION

UN Number: 3295
Packing Group: Class 3 Flammable Liquids
Group III (has a flash point from 23⁰C up to 60,5⁰C)
Proper Shipping Name: Hydrocarbon liquids

15. REGULATORY INFORMATION

Observe the general regulations when handling chemicals.
Contact your national regulations officer.

16. OTHER INFORMATION

Although the information contained in this publication is presented in good faith and to the best knowledge and experience of Reکارا Mills (Pty) Ltd, it is made without any warranty or guarantee whatsoever.

Updated: 01/08/05 Rev 1