

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

Product name: Woodoc Stain Concentrate
(Ebony, Imbuia, Meranti, Oak, Oregon, Rosewood,
Teak, Yellowwood)

Product type: Wood colourant

2. COMPOSITION

Blend of Pigments

Hazardous components: White spirit (5-10% by weight)

3. HAZARDS IDENTIFICATION

Flammability: Flammable

Potential Health effects and main symptoms:

Skin contact: May irritate skin. May dissolve fat on skin and cause dermatitis after prolonged and/or repeated contact. *Effect is not likely during normal use of product.*

Eye contact: May cause eye irritation.

Inhalation (Breathing): May cause respiratory irritation, dizziness, headache, nausea or loss of consciousness at very high vapour level. *Vapour level unlikely to reach these concentrations in normal use of product.*

Ingestion (Swallowing): May cause nausea, vomiting, stomach cramps and diarrhoea.

Acute over-exposure: May cause nausea, vomiting, headache, depression and loss of consciousness. *Not likely to occur under normal conditions of use.*

Chronic over-exposure: No chronic effects have been reported.

4. FIRST-AID MEASURES

- Ingestion (swallowing):** Do not induce vomiting. Have victim drink 240-300 ml water. Obtain medical attention.
- Skin contact:** Wash gently and thoroughly with water and soap.
- Eye contact:** Flush eye(s) with gently flowing lukewarm water for at least 15 minutes. Obtain medical advice.
- Inhalation (breathing):** If breathing is affected, remove victim to fresh air and call physician.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media:** Foam, CO₂, dry chemical.
- Unsuitable extinguishing media:** Water jets.
- Protection of fire-fighters:** Full protective clothing and self-contained apparatus required.
- Additional information:** Apply cold water in order to cool containers exposed to danger.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:**
- Eye/Face/Body:** Protective clothing (overall) should be worn.
- Hands:** Use leather gloves as they provide heat insulation and do not absorb oil.
- Environmental precautions:** Prevent material from entering sewers and waterways.
- Methods for cleaning up:** Contain and collect spillage with sand, vermiculite or other non-combustible absorbent material. Place in container for disposal according to local regulations.
- Additional instructions:** Inform authorities in case of large amount leakage.

7. HANDLING AND STORAGE

- HANDLING:**
- Safe handling advice:** Usual precautions for handling chemical substance. Consider common hygiene measures for handling chemical substance.
- STORAGE:**
- Storage conditions:** Store under cover, in a cool, dry place in original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures: General ventilation should be provided to maintain ambient concentration below nuisance levels.

Personal protection:

Skin: Wear cotton overalls when handling.
Hand: Use of rubber gloves recommended.
Eye/Face: Eye protection against splashes is recommended.
Respiratory: Air supplied mask.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Free Flow Liquid
Colour: Dependant on specific colour
Odour: With characteristic odour
Density at 20⁰C: > 1.0 Dependant on specific colour
Physical state: Liquid
Flash point: Not less than 41⁰C
Flammability: Flammable
Solubility in water: Insoluble
Solubility in solvent: Soluble in aliphatic solvents

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions.

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced. Keep away from oxidising agents, strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

13. DISPOSAL CONSIDERATIONS

Waste: Special waste incineration or by other modes of disposal in compliance with local legislation.

Contaminated packaging: Should be treated equivalent to residual chemical.

14. TRANSPORT INFORMATION

UN Number: 1263

Packing Group: Class 3 Flammable Liquids
Group III (has a flash point from 23⁰C up to 60,5⁰C)

Proper Shipping Name: Paint related material

15. REGULATORY INFORMATION

Observe the general regulations when handling chemicals.
Contact your national regulations officer.

16. OTHER INFORMATION

Although the information contained in this publication is presented in good faith and to the best knowledge and experience of Rekara Mills (Pty) Ltd, it is made without any warranty or guarantee whatsoever.

Updated: 01/08/05 Rev 1