

Woodoc 5 Specification Sheet



Typical Application:

Woodoc 5 creates an absolute matt or natural looking surface. Apply Woodoc 5 to hardwood tables, chairs, other furniture and interior woodwork where the beauty of a natural "oiled" look is required, but with a tough heat, stain and scratch resistant finish.

Product Features:

Woodoc 5 creates an absolute matt or natural looking surface that is nevertheless totally stain, water, alcohol and mark resistant. Woodoc 5 may be applied to previously waxed or oiled wood, and will not bubble, "feather" or flake. Clean previously oiled or waxed surfaces with Woodoc SteelWool and mineral turpentine before applying Woodoc 5.

- Easy to apply and "fail safe" for all users, from a large factory to the occasional hobbyist.
- Penetrates to form a durable layer of sealed wood that minimizes marring and facilitates easy restoration of damaged surfaces.
- Bubble and flake free.
- Penetrates to become part of the wood.
- Imparts a distinctive deep lustre and patina to all wood surfaces.
- Suitable for all types of wood.
- Non-toxic once dry.
- Does not affect glue.

No: WD5/002

Dated: 01/10/04 **Replacing:** New

Name:

Woodoc 5 - Indoor Matt Polywax Sealer

Description:

A natural "oiled" finish.

Coverage:

First coat 10-12m²/litre. Subsequent coats 12-14m²/litre. 3 coats (average) 3,3m²/litre.

Application:

Preferably by brush. Clean brush with mineral turpentine.

Dilution:

Not recommended.

Drying Time:

Sand: 3 - 6 hours.

Hard: 6 - 12 hours.

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear, lead-free, indoor wood sealer, with non-toxic preservative and anti-fungal properties. Formaldehyde free.

Wax Content:

High

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging:

500 ml, 1 litre and 5 litres.

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of the reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com