

# Woodoc Deck Dressing Specification Sheet



## Typical Application:

Woodoc Deck Dressing is a tinted, matt oil finish for application to hard, dense timber decking like Balau, Rhodesian Teak, Garapa or Iroko. It provides UV protection and is water repellent. Also suitable for roughly-sawn wood, eg. wendy houses and fences. Recommended re-application: every 6 months or when wood looks dry. Woodoc Deck Sealer is available in Rich Meranti, Deep Brown and Golden Brown.

## Product Features:

Woodoc Deck Dressing is oil based with added transparent iron oxides to protect wood against harsh sunlight.

- Excellent wind, water, pollution and salt spray protection.
- Incorporates a special drying oil that remains flexible, preventing surface cracking associated with temperature variation.
- Superior Ultra-violet radiation protection in extreme conditions.
- Low build characteristic for a smooth and attractive matt surface.
- Penetrates to nourish wood and combat fungal growth.
- Biodegrades at the end of its life cycle.
- No need for scraping or sanding. Clean the old surface with Woodoc SteelWool and mineral turpentine before re-applying Woodoc Deck Dressing.

**No:** WDD/001

**Dated:** 12/02/08 **Replacing:** New

## Name:

Woodoc Deck Dressing – Exterior Matt Oil Finish (Rich Meranti / Deep Brown / Golden Brown)

## Description:

Tinted, matt finish with UV protection and water repellence, for outdoor use.

## Coverage:

First coat 10-12m<sup>2</sup>/litre. Subsequent coats 12-14m<sup>2</sup>/litre. 3 coats (average) 3,3m<sup>2</sup>/litre.

## Application:

By brush. Clean brush with mineral turpentine.

## Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

## Drying Time:

The different coats may take up to 48 hours to dry, depending on the weather. **Caution:** As the product does not form a hard film on the surface, shoes and furniture cushions could be affected for at least 48 hours after application.

## Product Properties:

Tinted, matt, exterior wood deck dressing with preservative and anti-fungal properties.

## Wax Content:

None.

## Compatibility:

Mineral Turpentine.

## Non-Compatibility:

Acetone, Lacquer Thinners, Benzene, and other solvents.

## Packaging:

1 litre and 5 litres.

**ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.**

**FLAMMABLE. Keep out of the reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.**

**IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.**



Manufactured and marketed by:  
Rekara Mills (Pty) Ltd  
PO Box 16, Fort Beaufort 5720, South Africa  
Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll free during office hours 0800 411 200 (South Africa only)  
Email: [information@woodoc.com](mailto:information@woodoc.com) or visit [www.woodoc.com](http://www.woodoc.com)