

Woodoc 35 Specification Sheet



Typical Application:

For exterior use where a tinted low-gloss sealer is required. Provides UV-protection and is water repellent. Ideal for doors, window frames, garage doors and wooden garden furniture. **Not suitable for use on decks.**

Product Features:

Woodoc 35 is a tinted, exterior low-gloss sealer with transparent iron oxides and a UV-absorber, which provide extra protection against harsh sunlight. The product is moisture repellent and also contains a that feeds the wood.

- Protects exterior wood against seasonal and environmental moisture variation.
- Extra protection against ultra-violet radiation.
- Available in three tints: Meranti, Russet and Dark Brown.
- Suitable for all wood types.
- Deep penetrates to nourish wood.
- Non-toxic when dry.
- Does not affect glue.
- Biodegrades at the end of its life cycle.
- Complete how-to-use instructions on label.

No: WD35/003

Dated: 01/11/11

Name:

Woodoc 35 - Exterior Polywax Sealer (Meranti / Dark Brown / Russet)

Description:

Deep penetrating, tinted, low-gloss finish with extra UV-protection and water repellence, for outdoor use.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

By brush. Clean brush with mineral turpentine.

Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Tinted, low-gloss, exterior wood sealer. Formaldehyde-Free

Wax Content:

Low.

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging:

500 ml, 1 litre and 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:
Rekara Mills (Pty) Ltd
PO Box 16, Fort Beaufort 5720, South Africa
Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com