

# Woodoc 25 Specification Sheet



## Typical Application:

Woodoc 25 Satin is a clear floor sealer suitable for application to all indoor wooden floors and stairs.

## Product Features:

Woodoc 25 Satin is a clear, remarkably tough, wear resistant floor sealer. It imparts a distinctive natural sheen to floors, and creates a deep natural "polished" look that enhances the colour and grain of all woods.

- Protects against scratching.
- Will not chip or flake.
- Applies easily leaving no brush marks.
- Fills the grain of open-grained woods.

**NOTE:** Wooden floors should preferably not be washed with water and detergent. Clean with Woodoc Penetrating Furniture Wax or apply Woodoc Antique Wax.

**No:** WD25/002

**Dated:** 01/10/04 **Replacing:** New

## Name:

Woodoc 25 - Polyurethane Floor Sealer - Satin Finish.

Clear or Oregon Tinted

## Description:

Deep "polished" grain filling finish

## Coverage:

First coat 10-12m<sup>2</sup>/litre. Subsequent coats 12-14m<sup>2</sup>/litre. 3 coats (average) 3,3m<sup>2</sup>/litre.

## Application:

Preferably by brush. Clean brush with mineral turpentine.

## Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

## Drying Time:

**Sand:** 3 - 6 hours.

**Hard:** 6 - 12 hours.

Drying will vary, depending on moisture and atmospheric conditions.

## Product Properties:

Clear or Oregon tinted, lead-free, indoor wood sealer, with non-toxic preservative and anti-fungal properties.

Contains no formaldehyde.

## Wax Content:

None.

## Compatibility:

Mineral Turpentine.

## Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

## Packaging:

500 ml, 1 litre and 5 litres.

**ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.**

**FLAMMABLE.** Keep out of the reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

**IMPORTANT:** This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll free during office hours 0800 411 200 (South Africa only)

Email: [information@woodoc.com](mailto:information@woodoc.com) or visit [www.woodoc.com](http://www.woodoc.com)