

Woodoc Penetrating Weatherproof Wax Specification Sheet



Typical Application:

Woodoc Penetrating Weatherproof Wax is a deep penetrating maintenance wax for outdoor use on previously oiled, sealed or varnished surfaces. The period between applications depends on the environmental conditions in which it is used.

Product Features:

Woodoc Penetrating Weatherproof Wax penetrates the existing sealer or coating and replenishes the UV absorber of the old coating whilst enhancing the external appearance and feeding the wood. The wax content helps exclude moisture and combats fungus growth, whilst the UV absorber replenishes the sealer's UV resistance.

Advantages:

- Enhances the protection of wood against seasonal and environmental changes.
- Brings out the natural colour and grain of wood.
- Revitalises the surface coating, cleaning and refreshes it.
- Does not affect the strength of wood.
- Does not affect glue.
- Compatible with all varnishes, sealers and finishes.
- Unlimited shelf life.

No: WDpwwax/001

Dated: 20/01/03 **Replacing:** New

Name:

Woodoc Penetrating Weatherproof Wax

Description:

Exterior woodwork maintenance and refurbishing wax.

Coverage:

Dependant on application.

Application:

By brush or cloth.

Drying Time:

Not Applicable.

Product Properties:

A clear liquid wax formulated for maximum penetration.

Flashpoint (closed cup) 50°C.

Solidifies at 6°C, and wax precipitates at 18°C.

Density @ 20°C: 0,75 (water = 1)

Lead free. No hazardous decomposition materials.

Flammable.

Wax Content:

High

Should not be thinned.

Packaging:

375 ml, 1 litre, 5 litres, 200 litres.

*Shake before use. Keep out of the reach of children.
Harmful when consumed. Ingestion may cause chemical pneumonitis.*



Manufactured and marketed by:
Rekara Mills (Pty) Ltd
PO Box 16, Fort Beaufort 5720, South Africa
Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com