

Woodoc 55 Specification Sheet



Typical Application:

Woodoc 55 is a tinted, gloss, exterior sealer for use where a high build-up of sealer is required for additional ultra-violet protection. Woodoc 55 is available in Meranti, Dark Brown and Russet. It is used extensively on yachts, boats and all exterior woodwork on buildings exposed to conditions of harsh weathering.

Product Features:

Woodoc 55 is alkyd based with UV absorbers with added transparent iron oxides to protect wood against harsh sunlight.

- Excellent wind, water, pollution and salt spray protection.
- Incorporates a special alkyd base that remains flexible, preventing surface cracking associated with temperature variation.
- Superior Ultra-violet radiation protection in extreme conditions.
- High build characteristic for a smooth gloss surface.
- Deep penetrates to nourish wood and combat fungus growth.
- Biodegrades at the end of its life cycle.
- No need for scraping or sanding. Clean the old surface with Woodoc SteelWool and mineral turpentine before re-applying Woodoc 55.

No: WD55/002

Dated: 01/10/04 Replacing: New

Name:

Woodoc 55 - Exterior Gloss Sealer (Meranti / Dark Brown / Russet)

Description:

Deep penetrating, tinted, gloss finish with UV protection and water repellence, for outdoor use.

Coverage:

First coat 10-12m²/litre. Subsequent coats 12-14m²/litre. 3 coats (average) 3,3m²/litre.

Application:

By brush. Clean brush with mineral turpentine.

Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

Drying Time:

Sand: 6 - 12 hours.

Hard: 12 - 24 hours.

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Tinted, gloss, high build, exterior wood sealer with preservative and anti-fungal properties.

Wax Content:

None.

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene, and other solvents.

Packaging:

500 ml, 1 litre and 5 litres.

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of the reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com