

Woodoc 45 Specification Sheet



Typical Application:

For interior/exterior use on unglazed porous substrates like unsealed tiles, cement, stone and brick. It gives a clear, gloss finish.

Product Features:

- Strong, durable surface finish.
- Water-repellent.
- Stain- and oil resistant.
- Easy to use.
- Easy to clean brushes and equipment with water.
- Environment-friendly.
- Complete how-to-use instructions on label.

No: WD 45/003

Dated: 04/11/11

Name: Woodoc 45 – Tile and Cement Sealer

Description: Water-based tile and cement sealer for unglazed porous substrates.

Coverage: 5 – 12 m² per litre, depending on porosity of substrate.

Application: With paint brush. Clean brushes with water immediately after use.

Dilution: Not recommended

Drying Time: 2 – 4 hours. Allow 24 hours before surfaced is used.

Product Properties: Clear, water-based tile and cement sealer.

Wax Content: None

Compatibility: Water

Packaging: 1 litre, 5 litre. (20 or 200 litres available on request from dealer)



Manufactured and marketed by:
Rekara Mills (Pty) Ltd
PO Box 16, Fort Beaufort 5720, South Africa
Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com

Copyright © Woodoc 2005. All Rights Reserved.