

Woodoc Transit Stabilizer



Typical Application:

A preparation-free primer to protect exterior wood from manufacture to final finish. Provides essential protection for on-site wooden window frames, doors, doorframes and any other woodwork.

Product Features:

One thorough application as soon as possible after manufacture protects wood against on-site soiling. It will prevent wood from warping during transit and while building. Woodoc Transit Stabilizer also helps prevent cement burn from plaster.

- Easy to apply by brush.
- Spreads easily, leaving no brush strokes.
- Also suitable for dip application.
- Does not affect glue.
- Suitable for all types of wood.
- Penetrates to become part of the wood.
- Does not produce a surface layer and for a final finish, seal wood within 30 days with one of the Woodoc Exterior Sealers.
- Complete how-to-use instructions on label.

No: WDTransit/002

Dated: 23/11/11

Name:

Woodoc Transit Stabilizer
(Clear or Meranti-tinted)

Description:

Primer to protect exterior wood on-site.

Application:

Brush, dip or spray.

Drying Time:

Not Applicable

Product Properties:

Dimensionally stabilizing primer for untreated lumber and joinery.

Compatibility:

Mineral Turpentine

Packaging:

5 litres. (200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.
FLAMMABLE. Keep out of reach of children. Harmful if ingested. Ingestion may cause chemical pneumonitis.



Manufactured and marketed by:
Rekara Mills (Pty) Ltd
PO Box 16, Fort Beaufort 5720, South Africa
Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)
Email: information@woodoc.com or visit www.woodoc.com