

# Woodoc 25 Satin Specification Sheet



## Typical Application:

Suitable for application to all interior wooden floors and -stairs. Only for interior use. Resistant to normal domestic wear and tear.

**Woodoc 25 is not an industrial product.**

## Product Features:

Woodoc 25 Satin creates a clear or Oregon-tinted glossy finish. It is a remarkably tough, wear-resistant floor sealer and lends a characteristic deep polished look to floors.

- Water-, alcohol-, heat- and stain-resistant.
- Easy application.
- Penetrates wood, binds with it and lends a flexible yet strong and resistant surface finish.
- Suitable for all types of wood.
- Non-toxic once dry.
- Fills the grain of open-grained woods.
- Floor surface can be slippery after sealing with this product.
- Complete how-to-use instructions on label.

**NOTE:** Wooden floors treated with Woodoc 25 should not be washed with water and detergents/soap. Clean with Woodoc Deep Penetrating Furniture Wax or apply Woodoc Antique Wax and polish.

**No:** WD25/008

**Dated:** 03/10/19

**Name:**

Woodoc 25 - Polyurethane Floor Sealer - Satin Finish.

Clear or Oregon Tinted

**Description:**

Deep "polished" grain-filling finish

**Coverage:**

First coat 10-12 m<sup>2</sup>/litre. Subsequent coats 12-14 m<sup>2</sup>/litre. 3 coats (average) 3,3 m<sup>2</sup>/litre.

**Application:**

Preferably by brush. Clean brush with mineral turpentine.

**Dilution:**

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

**Drying Time:**

Drying will vary, depending on moisture and atmospheric conditions.

**Product Properties:**

Clear or Oregon-tinted, lead-free, indoor wood sealer. Formaldehyde-Free.

**Wax Content:**

None.

**Compatibility:**

Mineral Turpentine.

**Non-Compatibility:**

Acetone, Lacquer Thinners, Benzene and other solvents.

**Packaging:**

**Clear:** 500 ml, 1 litre, 2,5 litres and 5 litres. (20 or 200 litres available on request from dealer)

**Oregon:** 1 litre, 2,5 litres and 5 litres. (20 litres available on request from dealer)

**ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.**

**FLAMMABLE.** Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

**IMPORTANT:** This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

Email: [information@woodoc.com](mailto:information@woodoc.com) or visit [www.woodoc.com](http://www.woodoc.com)