

Woodoc 55 Specification Sheet



Typical Application:

For exterior use where a tinted, gloss sealer is required. Provides UV-protection and is water repellent. It is used extensively on yachts, boats and all exterior woodwork on buildings exposed to conditions of harsh weathering.

Not suitable for use on hard, dense wooden decks.

Product Features:

Woodoc 55 is a tinted, exterior gloss sealer with UV-absorbers and added transparent iron oxides to protect wood against harsh sunlight.

- Excellent protection against wind, water, pollution and salt spray.
- Contains a special alkyd base that remains flexible, preventing surface cracking associated with temperature variation.
- Superior Ultra-violet radiation protection in extreme conditions.
- High-build characteristic for a smooth gloss surface.
- Available in three tints: Meranti, Russet and Deep Brown.
- Suitable for all wood types.
- Non-toxic when dry.
- Deep penetrates to nourish wood.
- Biodegrades at the end of its life cycle.
- Complete how-to-use instructions on label.

No: WD55/004

Dated: 03/10/19

Name:

Woodoc 55 - Exterior Gloss Sealer (Meranti / Dark Brown / Russet)

Description:

Deep penetrating, tinted, gloss finish with UV protection and water repellence, for outdoor use.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

By brush. Clean brush with mineral turpentine.

Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Tinted, gloss, high-build, exterior wood sealer.

Formaldehyde-Free

Wax Content:

None.

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene, and other solvents.

Packaging:

500 ml, 1 litre and 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com