

Totim Exterior Wood Sealer Specification Sheet



Typical Application:

For exterior use where a durable weatherproof finish is required. Provides UV-protection and is water-repellent. Also suitable for use on roughly sawn wood, e.g. wendy houses and fences. **Not suitable for use on interior woodwork.**

Product Features:

Totim Exterior Wood Sealer is a clear or tinted exterior sealer with transparent iron oxides and UV-absorbers, which provide extra protection against harsh sunlight.

- Protects exterior wood against seasonal and environmental moisture variation.
- Extra protection against ultra-violet radiation.
- Available in four tints: Pine, Mahogany, Teak and Golden Brown.
- Also available in Clear.
- Suitable for all wood types.
- Provides a low-gloss finish.
- Deep penetrates to nourish wood.
- Non-toxic when dry.
- Biodegrades at the end of its life cycle.
- Complete how-to-use instructions on label.

No: Totim SB/004

Dated: 21/04/22

Name:

Totim Exterior Wood Sealer
(Clear/Pine/Mahogany/Teak/Golden Brown)

Description:

Deep-penetrating, clear or tinted, low-gloss finish with extra UV-protection and water repellence, for exterior use.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

By brush. Clean brush with mineral turpentine.

Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear, or tinted low-gloss, exterior wood sealer. Free of Formaldehyde and Lead.

Wax Content:

Low.

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging:

1 litre and 5 litres. (20- or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis. **IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.**



Manufactured and marketed by:
Rekara Mills (Pty) Ltd
PO Box 16, Fort Beaufort 5720, South Africa
Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)
Email: information@woodoc.com or visit www.woodoc.com