

# Totim Water-Borne™ Exterior Wood Sealer Specification Sheet



## Typical Application:

A water-borne exterior sealer that is ideal for all exterior wooden surfaces exposed to severe weather conditions. Provides excellent UV-protection and is water repellent. Suitable for use on exterior wood like fences, garden furniture, doors, window frames, garage doors and decks.

## Product Features:

Totim Water-Borne Exterior Wood Sealer is a water-borne tinted or clear exterior sealer with transparent iron oxides and a UV-absorber, which provide extra protection against harsh sunlight.

- Protects exterior wood against seasonal and environmental moisture variation.
- Extra protection against ultra-violet radiation.
- Available in four tints: Mahogany, Teak, Golden Brown and Imbuia .
- Also available in Clear.
- Suitable for all wood types.
- Provides a low-gloss finish.
- Deep penetrates to nourish wood.
- Non-toxic when dry.
- Walking surfaces can be slippery after sealing with this product.
- Biodegrades at the end of its life cycle.
- Complete how-to-use instructions on label.

**No:** Totim WB/003

**Dated:** 18/07/19

## Name:

Totim Water-Borne Exterior Wood Sealer (Clear/Mahogany/Teak/Golden Brown/Imbuia)

## Description:

Deep penetrating, tinted or clear low-gloss finish with extra UV-protection and water repellence, for exterior use.

## Coverage:

First coat 10-12 m<sup>2</sup>/litre. Subsequent coats 12-14 m<sup>2</sup>/litre. 3 coats (average) 3,3 m<sup>2</sup>/litre.

## Application:

By paint brush. Clean brush with water before brush dries.

## Dilution:

Dilution is not recommended.

## Drying Time:

4 – 6 hours between coats.

Drying will vary, depending on moisture and atmospheric conditions.

## Product Properties:

Tinted or clear, low-gloss, water-borne exterior wood sealer. Free of NMP, Formaldehyde and Lead.

## Wax Content:

None.

## Compatibility:

Water.

## Non-Compatibility:

Acetone, Lacquer Thinners, Mineral Turpentine, Benzene and other solvents.

## Packaging:

1 litre and 5 litres. (20 litres available on request from dealer)

**ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE APPLICATION.**

**IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.**



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +27 46 645 1109 Fax +27 46 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

Email: [information@woodoc.com](mailto:information@woodoc.com) or visit [www.woodoc.com](http://www.woodoc.com)