


Woodoc Water-Borne Plus-Life™ PRIMER Specification Sheet



Typical Application:

Woodoc Water-Borne Plus-Life™ PRIMER is a performance enhancing primer for Woodoc Water-Borne Exterior Sealers. This product should always be overcoated with a Woodoc Water-Borne Exterior Sealer.

Product Features:

- Prepares wooden surface for sealing.
- Extends the life of the sealer.
- The Primer should always be overcoated with a Woodoc Water-Borne Exterior Sealer.
- Suitable for all types of wood.
- Non-toxic once dry.
- Complete how-to-use instructions on label.

No: WD WB Plus-Life™ PRIMER /003

Dated: 02/11/16

Name:

Woodoc Water-Borne Plus-Life™ PRIMER – Clear.

Description:

Prepares wood for sealing.

Coverage:

10-12 m²/litre.

Application:

Preferably by brush. Clean brush with water before dry.

Dilution:

Do not dilute product.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions. Surface dry: 1 Hour.

Product Properties:

Clear, lead-free, exterior water-borne wood primer. Formaldehyde-Free. NMP-Free.

Wax Content:

None.

Compatibility:

Water.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

VOC: This product contains max. 30 g/l VOC.

Packaging: 1, 2,5 and 5 litres. (20 litres available on request)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com