

# Woodoc 30 Specification Sheet



## Typical Application:

For exterior use where a low-gloss, clear wood sealer is required. Provides UV-protection and is water-repellent. Ideal for doors, window frames, garage doors and garden furniture.

**Not suitable for use on decks.**

## Product Features:

Woodoc 30 is an exterior, low-gloss, clear sealer that enhances the natural appearance and colour of wood. The product is moisture-repellent, has a wax fraction that feeds the wood, as well as UV-absorbers that protect the wood against the sun's rays.

- Protects exterior wood against seasonal- and environmental moisture variation.
- Offers excellent protection against ultra-violet radiation.
- Enhances the grain and natural colour of the wood.
- Suitable for all wood types.
- Deep penetrates to nourish wood.
- Non-toxic when dry.
- Biodegrades at the end of its life cycle.
- Complete how-to-use instructions on label.

**No:** WD30/008

**Dated:** 27/02/24

**Name:**

Woodoc 30 - Exterior Polywax Sealer

**Description:**

Deep penetrating, low-gloss, clear finish with UV-protection and water repellence for exterior use.

Low Gloss, Clear.

**Coverage:**

± 10 m<sup>2</sup>/litre per coat (± 3,3 m<sup>2</sup>/litre for 3 coats).

**Application:**

Paintbrush. Clean brush with mineral turpentine.

**Dilution:**

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

**Drying Time:**

Drying will vary, depending on moisture- and atmospheric conditions.

**Product Properties:**

Low-gloss, clear, exterior wood sealer.

Lead- and Formaldehyde-Free.

**Wax Content:** Low.

**Compatibility:** Mineral Turpentine.

**Non-Compatibility:**

Acetone, Lacquer Thinners, Benzene and other solvents.

**Packaging:**

500 ml, 1 litre, 2,5 and 5 litres (20 or 200 litres available on request from dealer).

**ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.**

**FLAMMABLE.** Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

**IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.**



Manufactured in South Africa by:

Rekara Mills (Pty) Ltd

242 Main Road, Walmer, Port Elizabeth (Gqeberha)

PostNet suite #29, Private Bag x0002, The Fig Tree, CHARLO,

Port Elizabeth (Gqeberha), 6033

Customer Service:

Toll-Free during office hours: 0800 411 200 (South Africa only)

International: +27 41 555 0007 (Office Hours only)

E-mail: [information@woodoc.com](mailto:information@woodoc.com) or visit [www.woodoc.com](http://www.woodoc.com)

WhatsApp: +27 66 302 4702