

Woodoc 45 Specification Sheet



Typical Application:

For interior/exterior use on unglazed, porous substrates like unsealed tiles, -cement, -stone and -brick. It lends a gloss/matt, clear finish. Provides UV-protection and is water-repellent.

Product Features:

- Does not yellow.
- Strong, durable surface finish.
- UV-resistant and water-repellent.
- Resistant to stains and oil.
- Easy to use.
- Easy to clean brushes and equipment with water.
- Environment-friendly.
- Complete how-to-use instructions on label.

No: WD 45/008

Dated: 20/02/25

Name: Woodoc 45 – Tile and Cement Sealer

Description: Water-borne tile and cement sealer for unglazed, porous substrates. Gloss/Matt, Clear.

Coverage: 5 – 12 m² per litre, depending on porosity of substrate.

Application: Paintbrush. Clean brushes with water immediately after use.

Dilution: Not recommended.

Drying Time: 2 – 4 hours. Allow 24 hours before surfaced is used.

Product Properties: Gloss/Matt, clear, water-borne tile and cement sealer. Formaldehyde-Free. NMP-Free.

Wax Content: None.

Compatibility: Water.

Packaging: 1 litre, 5 litres (20 litres available on request from dealer).

ALWAYS READ THE DIRECTIONS ON THE CONTAINER BEFORE STARTING WORK.



Manufactured in South Africa by:
Rekara Mills (Pty) Ltd
242 Main Road, Walmer, Port Elizabeth (Gqeberha)
PostNet suite #29, Private Bag x0002, The Fig Tree, CHARLO,
Port Elizabeth (Gqeberha), 6033

Customer Service:

Toll-Free during office hours: 0800 411 200 (South Africa only)

International: +27 41 555 0007 (Office Hours only)

E-mail: information@woodoc.com or visit www.woodoc.com

WhatsApp: +27 66 302 4702