

Application Instructions

Woodoc 20 Polyurethane Sealer Interior

WHERE TO USE PRODUCT

For interior use only. Use on wooden furniture, -doors, -countertops, other interior wood. Resistant to water, alcohol, heat, cold and scratches. Strong, hard finish. Grain-filling.

HOW TO PREPARE THE SURFACE

General: Wood must always be clean, dry & smooth before use of product. Never wash/wipe wood with water before use of product.

New wood: Sand until smooth. Remove dust with clean, dry cloth. Then wipe with mineral turpentine.

Previously varnished wood: Sand until bare and smooth. Start with a coarse grit sandpaper and end with a fine grit. Remove dust with clean, dry cloth. Then wipe with mineral turpentine. The use of paint strippers is not recommended.

Oiled wood: Scrub well with Woodoc SteelWool and mineral turpentine. Sand until smooth. Clean with Woodoc SteelWool and mineral turpentine again. Wipe off residue with clean, dry cloth. Allow surface to dry.

Wood previously treated with this product: Scrub well with Woodoc SteelWool and mineral turpentine. Clean off residue with clean, dry cloth. Allow surface to dry.

Weathered wood: Sand weathered wood to remove all traces of weathering or use Woodoc Wood Reviver according to instructions.

HOW TO APPLY THE PRODUCT

Stir well with flat paddle before and during application. Do not shake or dilute product. **Always apply a minimum of three coats to new wood.** Apply product with good-quality brush. Apply first coat until surface remains evenly glossy for at least 10 minutes after application. Apply more product to dull/dry areas. Allow coat to dry **completely**. Sand lightly with Woodoc SteelWool. Remove dust with clean, dry cloth. Then wipe with mineral turpentine. Apply two more coats in the same way. Do not sand after third coat.

COVERAGE

± 10 m²/litre per coat (± 3,3 m² per litre for 3 coats)

WARRANTY

Rekara Mills (Pty) Ltd warrants that this product, as consigned from our factory, was subject to strict quality assurance tests and meets durability-, safety- and quality standards. The product must be used, stored and handled strictly according to the instructions and warnings provided on the container and/or any pamphlet attached thereto or made available with the product. All such instructions and warnings must be strictly adhered to otherwise Rekara Mills (Pty) Ltd accepts no responsibility for the use of performance of this product.